20 mm x 0.76 mm STAINLESS STEEL BANDING AND BUCKLE (4) PLACES

TO CROSS
(ARROW OR STREET NAME)
PUSH BUTTON

START CROSSING
WATCH FOR TURNING CARS

DON'T START
FINISH CROSSING IF STARTED
FLASHING

PEDESTRIANS
SHOULD NOT BE IN CROSSWALK
STEADY

PEDESTRIAN SIGN
115 mm

150 mm

PEDESTRIAN PUSH BUTTON
INSTALL BUSHING IN HOLE
FOR PEDESTRIAN BUTTON WIRES.
INSTALL DUCT SEAL MATERIAL
BETWEEN PEDESTRIAN BUTTON
HOUSING AND POLE

GROUNDING LUG

75 mm x 150 mm HANDHOLE WITH
REINF. FRAME & COVER

DRIVING HEAD CLAMP

CAST LEAVES OR ACORN NUTS

CAST BASE OR PLATE

SIDEWALK OR GROUND LINE

CLASS "A" CONCRETE

50 mm DIA. GALVANIZED
STEEL CONDUIT

20 mm x 762 mm ANCHOR
BOLTS & (4) HEX NUTS AND (4)
SQUARE LEVELING NUTS

16 mm x 5.5 m
COPPERWELD OR HOT DIPPED
GALVANIZED GROUND ROD

2.5 m

75 mm

1050 mm

1.2 m

600 mm
(SQUARE)

PEDESTRIAN SIGNAL POLE WITH STANDARD PEDESTRIAN SIGNAL

NOT TO SCALE

7/14/00

REVISED